



MODEL J5N 33.420 FT

6x4 TRUCK TRACTOR

CAB

Cab Control Forward Tilt Cab Driver + 1 Passenger Seating Sleeper cab with Aircon, Radio Type/Extras with USB, Suspension seat


ENGINE

Make & Model WP 12.420E32 Capacity 11 600 cm³ 6 cylinder in line, water cooled, Layout & Type turbo charged & intercooled Euro II

Emissions Standard Power @ r/min (kW) Torque @ r/min (Nm)

309 @ 2 200 1 750 @ 1 300 - 1 400





TRANSMISSION

FAST C12JSDQXL200 Make & Model No of Gears 12 Speed Manual Syncromesh, 15.70, 12.25, 9.42, 7.43, 5.79, Forward Ratios 4.52, 3.47, 2.71, 2.08, 1.64, 1.28, 1.00 14.44;3.19 Reverse Ratio

CLUTCH

430 mm Diameter Туре Single Plate Hydraulic-Air Assisted Operation

STEERING

23:1 Gear Ratio Type Recirculating Ball Operation Power Assisted

PERFORMANCE

Gradeability @ V Max 27% Permissible Road Speed 80km/h

AXLES

| П | | |
|---|-----------------------------|----------------------------------|
| | Front Axle | I-Section Beam (forged steel) |
| | Rear Axle - Gearing Type | Full Floating - Single Reduction |
| ı | Rear Axle Ratio | 4.1:1 |

BRAKES

Full Air - Dual Circuit with ABS System Type Park/Emergency Spring Brakes/Rear Booster System

FUEL TANK

| Number | One |
|----------------|-----------|
| Total Capacity | 600 Litre |

ELECTRICAL SYSTEM

| System Voltage & Type | 24V Negative Earth |
|-----------------------|--------------------|
| No. of Batteries | Two X 12V |

CHASSIS

| Туре | Straight Ladder Type - Riveted |
|------------------|---|
| Front Suspension | Semi-Elliptical Leaf Springs with Double Acting Shock Absorbers |
| Rear Suspension | Semi-Elliptical Leaf Springs with Auxillary Springs |

WHEELS

| Tyre Size | 315/80 R22.5 18PR |
|-----------|-------------------|
| Rim Size | 9.00 x 22.5 |
| Туре | Tubeless Radial |

| MASS DATA | kg |
|---|--------|
| Manufacturer's Gross Vehicle Mass (GVM) | 33 700 |
| Manufacturer's Gross Combination Mass (GCM) | 62 200 |
| Manufacturer's Front Axle Mass (GA Front) | 7 700 |
| Manufacturer's Rear Axle Mass (GAU Rear) | 26 000 |
| Permissible Gross Vehicle Mass (V) | 25 700 |
| Permissible Gross Combination Mass (D/T) | 56 000 |
| Permissible Front Axle Mass (A Front) | 7 700 |
| Permissible Rear Axle Mass (A Rear) | 18 000 |
| Unladen Front Axle Mass (T Front) | 4 620 |
| Unladen Rear Axle Mass (T Rear) | 4 500 |
| Unladen Mass Total (Tare) | 9 120 |

| DIMENSIONS | mm |
|---------------------------|---------------|
| Wheelbase (WB) | 3 150 + 1 350 |
| Overall Length (OL) | 6 840 |
| Cab Length (A) | 2 470 |
| Overall Width (OW) | 2 500 |
| Overall Height (OH) | 3 450 |
| Front Overhang (D) | 1 493 |
| Rear Overhang (ROH) | 800 |
| Cab to Rear Axle (CA) | 3 173 |
| Cab to End of Chassis (F) | 4 650 |
| Minimum Turning Radius | 6 500 |
| Minimum Turning Diameter | 13 000 |
| Ground Clearance | 300 |
| Track - Front | 2 020 |
| Track - Rear | 1 830 |
| Chassis Outer Width | 800 |
| Chassis Inner Width | 640 |

The above specifications are not binding - subject to change without prior notice.

